

# Iridium Extreme 9575N



**Brand:** IRIDIUM  
**Product Code:** 11-103-011  
**Availability:** 5

**Price: Fr. 1598.00**

**Ex Tax: Fr. 1478.26**

## Short Description

Iridium 9575 is compact, light, and easy to use right out of the box-

## Description

Iridium 9575 is compact, light, and easy to use right out of the box. It's engineered to withstand rugged environments and connected to the only truly global mobile network — so you can depend on it as a communications lifeline whenever and wherever it's called for.

## Lieferumfang

- High performance battery 2'300 mAh
- Travel charger for mains operation incl. 5 adapters
- Mobile charger with lighter plug
- Protective cover
- USB data cable
- User Manual (English only)
- Quick Start Guide
- CD-ROM with software
- Accessory adapter (2x)
- Magnetic vehicle antenna with 1.5m cable
- Hand-free set with earphone and microphone

## Specifications

| Communication specs           |                                     |
|-------------------------------|-------------------------------------|
| Antenna type                  | Teleskop ausziehbar                 |
| Coverage                      | weltweit                            |
| Data transmission             | 2400 bit/s (komprimiert 9600 bit/s) |
| Frequency range               | 1616.0 - 1626.5 MHz                 |
| Provider                      | Iridium                             |
| Stand by time max.            | 30 h                                |
| Talking time max.             | 4 h                                 |
| Construction / technical data |                                     |
| Capacity                      | 2'300 mAh @ 3.7 V                   |
| Data connection               | Mini-USB                            |
| DC power voltage              | 10-32 V=                            |
| Dimensions LxWxD              | 140 x 60 x 27 mm                    |
| Display type                  | LCD                                 |
| Main power voltage            | 110-240 V~                          |
| Weight                        | 247 g                               |
| Environmental conditions      |                                     |
| Charging temperatures         | 0 °C bis +45 °C                     |
| Leak tightness                | IP65                                |
| Max. absolute altitude        | 12'192 m.ü.M = 40'000 ft            |
| Technical standards           | MIL-STD 810F                        |
| Temperature range             | -65 °C bis +71 °C                   |

## Product Gallery

